

## Inkjet Coding and Marking Equipment

## **Standard Features:**

- Dimensions: 12" x 60" x 1.50" Low Profile, with T-Solt Extrusions for Side Mounting. (inclds. screws).
- Drive Belt 11.90" (w), Black PVC, Low Friction.
- Drive Motor: 1/2HP Brushless DC, VERY Quiet/VERY Low Vibration. Digital Controller provides Variable– Speed (5-88 fpm) - 150lb Load Capacity.
- Leg Stand with Locking Wheel Casters, adjustable height 28" to 34", add 3.5" for caster height.
- UHMV Guide Rail with adjustable brackets, Rail has 1.25" Wide-Face with stainless backing 48" long. Brackets Adjusts max. height of 3.75", inside of frame 2.00"
- Also Includes; Mounting Screws, Mounting for Controller and 15-Foot Control Cable for remote connection of Dry-Contact Relays, etc. (Relays/Switches not Included).



Carpenter's [ Jime Systems **P:** (409) 838-5391 TF: (888) 838-5391 CarpentersTimeSystems.com InkjetCodingandMarking.com

## **Options:**



**Custom Lengths and Widths** 



**Custom Stands and Footings** 



Custom Guide-Rails



**Custom Belting:** 

Cleated, Food Grade, etc.